



MAXIWASH

Soft Mount Washer-Extractor



- Advanced microprocessor
- Large display screen
- 20 programs available
- USB transfer
- Easy to program, easy to control
- Support 8 different languages





TECHNICAL SPECIFICATIONS

Item	Unit	SXT-250FD/ZQ	SXT-150FD/ZQ
Load capacity	Kg	25	15
Drum diameter	mm	774	658
Drum depth	mm	534	438
Drum volume	L	251	149
Wash speed	r.p.m	45	46
Extract speed	r.p.m	860	900
G-force	G	320	300
Motor	KW	2.2	1.5
Electrical heating	KW	15	9
Door opening	mm	539*539	539*539
Floor to door	mm	880	808
Steam consumption	kg	< 20	< 12
Water inlet (2)	inch	1	3/4
Drain outlet	mm	51	51
Steam inlet	Inch	1/2	1/2
Net weight	Kg	720	480
Width	mm	1038	880
Depth	mm	1154	858
Height	mm	1466	1413

Features and Benefits

- Independent suspension structure
- Advanced electronic balancing technique achieves out of balance automated load adjustment.
- Free standing, soft mount, high speed 320G
- 5 External chemical injection ports
- Robust industrial design
- Durable door safety lock and handle
- Variable frequency drive
- Stainless steel construction
- Full mold production
- Internationally available components such as SUSPA shock absorber, NSK bearings, Depend O Drain valves, etc.