



MAXI STEAM HEATED Flatwork Ironer

Model: YZI-2200/2500/2800/3000/3300 (SINGLE ROLL)

YZII-2500/2800/3000/3300 (DOUBLE ROLLS)

YZIII-2800/3000/3300 (THREE ROLLS)

YZIIII-3000 (FOUR ROLLS)

YZ series flatwork ironers are designed for medium and big size laundries which can bring higher working efficiency and better ironing effect.

Features:

- 1- The roll is made of stainless steel
- 2- The transmission is adjusted through speed regulation; the working speed can be changed according to the heating temperature and the thickness of linen.
- 3- Adopt gear reducer to connect the pulley and chain wheels to accomplish stable and reliable work.
- 4- Seal: Sealed rotary joints prevent leakage, safety and reliability, save energy.
- 5- Protection devices: Three-phase electrical system, overload protection, voltage and short circuit protection, emergency stop switch, safety guard device on the front, etc.
- 6- With unique differential design and installation of ironing belts, it solves the ubiquitous problem of bad small linen ironing effect, and ironing wrinkle on both size of the roll.
- 7- The ironing belts adopt automatic tension technology which achieves the perfect ironing effect due to consistent tightness of belts.
- 8- Equipped with floating type steam trap, it has no request for the steam pressure difference, so it can drain smoothly.





Specifications:

Model	Unit	YZ I -2200	YZ I -2500	YZ I -2800	YZ I -3000	YZ I -3300
Max Ironing width	mm	2200	2500 2800		3000	3300
Number of roll	рс	1	1	1	1	1
Roll diameter	mm	800	800	800	800	800
Ironing Speed	m/min	0-6	0-6	0-6	0-6	0-6
Max heating temperature	$^{\circ}$	158	158	158	158	158
Steam pressure	Мра	0.4-0.6	0.4-0.6	0.4-0.6	0.4-0.6	0.4-0.6
Steam consumption	Kg/h	85	100	120	135	150
Motor power	kw	0.75	0.75	0.75	0.75	0.75
Rated voltage	Volt	380	380	380	380	380
Dimension(L.W.H)	mm	3400*1250*1250	3800*1250*1250	4000*1250*1250	4200*1250*1250	4400*1250*1250
Total weight	kg	1300	1350	1450	1500	1600







Model	Unit	YZII-2500	YZII-2800	YZII-3000	YZII-3300	YZIII-2800	YZIII-3000	YZIII-3300	YZIIII-3000
Max Ironing width	mm	2500	2800	3000	3300	2800	3000	3300	3000
Number of roll	рс	2	2	2	2	3	3	3	4
Roll diameter	mm	800	800	800	800	800	800	800	800
Ironing Speed	m/min	3-15	3-15	3-15	3-15	3-20	3-20	3-20	3-25
Max heating temperature	$^{\circ}$	158	158	158	158	158	158	158	158
Steam pressure	Мра	0.4-0.6	0.4-0.6	0.4-0.6	0.4-0.6	0.4-0.6	0.4-0.6	0.4-0.6	0.4-0.6
Steam consumption	Kg/h	140	160	180	220	240	260	280	340
Motor power	kw	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2
Rated voltage	Volt	380	380	380	380	380	380	380	380
Dimension(L.W.H)	mm	3700*2150*1420	4000*2150*1420	4200*2150*1420	4400*2150*1420	4000*3200*1420	4200*3200*1420	4400*3100*1385	4160*4500*1420
Total weight	kg	2700	2900	3200	3300	3500	3800	4000	5200


















MAXI ELECTRIC HEATED Flatwork Ironer

Model: YDI-2200/2500/2800/3000 (SINGLE ROLL) YDII-2500/2800/3000 (DOUBLE ROLLS)

YD series ELECTRIC HEATED flatwork ironers are designed for small and medium-size laundries to dry and iron all kinds of comforter, table cloth, towels, etc.

Features:

- 1- Electric heating
- 2- The roll is made of stainless steel.
- 3- The transmission is adjusted through speed regulation; the working speed can be changed according to the heating temperature and the thickness of linen.
- 4- Adopt gear reducer to connect the pulley and chain wheels to accomplish stable and reliable work.



opecijications:								
Model	Unit	YD I -2200	YD I -2500	YD I -2800	YD I -3000	YD I I -2500	YD ∐ -2800	YD ∐-3000
Max Ironing width	mm	2200	2500	2800	3000	2500	2800	3000
Number of roll	рс	1	1	1	1	2	2	2
Roll diameter	mm	800	800	800	800	800	800	800
Ironing Speed	m/min	0-6	0-6	0-6	0-6	0-6	0-6	0-6
Heating power	kw	32.4	36	43.2	43.2	72	86.4	86.4
Max heating temperature	$^{\circ}$	230	230	230	230	230	230	230
Motor power	kw	0.75	0.75	0.75	0.75	2.2	2.2	2.2
Rated voltage	Volt.	380	380	380	380	380	380	380
Dimension(L.W.H)	mm	3400*1250*1250	3700*1250*1250	4000*1250*1250	4200*1250*1250	3700*2150*1385	4000*2150*1385	4200*2150*1385
Total weight	kg	1300	1350	1400	1450	2500	2600	2700

